



PCT/GB 2004 / 0 0 4 1 2 1



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8EQ

22 OCT 2004

WIPO

PCT

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew Gersey

Dated 5 October 2004

BEST AVAILABLE COPY

Patents Form 1/77

Patents Act 1977
(Rule 16)

THE PATENT OFFICE
CF
26 SEP 2003
RECEIVED BY FAX



26SEP03 E840340-1 D02813

P01/7700 0-40-0322602.4

1777

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1.	Your Reference	P58809V-GB		
2.	Patent Application number (The Patent Office will fill in this part)	26 SEP 2003		0322602.4
3.	Full name, address and postcode of the or each applicant. (<u>underline all surnames</u>)	The BOC Group plc Chertsey Road Windlesham Surrey GU20 6HJ		
	Patents ADP Number (if you know it)	8599821001		
	If the applicant is a corporate body, give the country/state of its incorporation	United Kingdom		
4.	Title of the invention	Vent-Run Gas Switching Systems		
5.	Name of your agent (if you have one)	FRY HEATH & SPENCE LLP		
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	The Gables Massetts Road Horley Surrey RH6 7DQ United Kingdom		
	Patents ADP Number (if you know it)	96880275001 8599821001 GU20 6HJ		
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number.	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application.	Number of earlier application		Date of filing (day / month / year)
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:	Yes		
	a) any applicant named in part 3 is not an inventor; or			
	b) there is an inventor who is not named as an applicant; or			
	c) any named applicant is a corporate body			
	(See note (d))			

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Continuation sheets of this form 0

Description 8

Claim(s) 2

Abstract 1

Drawing(s) 1 only

10. If you are also filing any of the following, state how many against each item.

Priority documents 0

Translations of priority documents 0

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 0

Request for preliminary examination and search (Patents form 9/77) 1

Request for substantive examination (Patents form 10/77) 0

Any other documents (please specify) 0

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

Victoria J Townsend

26 September 2003

12. Name and daytime telephone number of person to contact in the United Kingdom Victoria J Townsend - 01293 776880

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you filing or applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

1

VENT-RUN GAS SWITCHING SYSTEMS

This invention relates to vent-run gas switching systems commonly used in atomic layer deposition (ALD) or chemical vapour deposition (CVD) techniques. In particular, the invention relates to an improvement to such systems which reduces the opportunity for cross-reaction between gases in such a system.

Vent-run gas switching systems are commonly used in the growth of multi-layer thin films. Two common example applications are the manufacture of Al_2O_3 and TIN films. In such applications, sources of two or more gaseous species to be deposited are provided, a purge gas source may also be provided. The gases are delivered to a process chamber sequentially, by means of a switching system between the gas sources and the process chamber. Any residual species, purge gas or by-products are exhausted from the process chamber by a pump.

Typically, a purge gas is passed through the reaction chamber between supplies of the species to be deposited. The purpose of the purge gas is to remove any residual (not deposited) species from the process chamber so as to prevent reaction with the next species supplied to the chamber. Were the species allowed to cross react, this might result in impurities and imperfections in the multi-layer film.

In existing vent-run gas switching systems, gases leaving the process chamber enter a common foreline leading to a vacuum pump. Cross reaction of any residual species can occur in the foreline and this can result in the accumulation of particulates in the foreline leading to impaired pump performance. Such impairment of pump performance may compromise the quality of the product manufactured in the process chamber. In addition, the process down time involved in repairing and maintaining affected pumps can increase the costs of manufacture.

The present invention aims to provide a vent-run gas switching system wherein cross reaction of species on exhaust from the process chamber is significantly reduced.

In accordance with the present invention there is provided a vent-run gas switching system comprising:

a plurality of gas supply conduits in fluid communication with a process chamber; a plurality of gas exhaust conduits in fluid communication with the process chamber; a plurality of pumps each in fluid communication with one or more gas exhaust conduits; a first valve system associated with the plurality of gas supply conduits and configured to control supply of a plurality of gases to the process chamber in sequence;

a second valve system associated with the plurality of gas exhaust conduits configured to direct gases exhausted from the process chamber to the pumps, each gas being selectively directable to a pre-selected pump; and

one or more gas supply bypass conduits in fluid communication with one or more of the pumps and bypassing the process chamber.

Optionally, the system further includes a controller for controlling the operation of the first and second valve systems, in use, to supply gases to the process chamber in a pre-selected sequence and exhaust gases, in sequence, to pre-selected pumps.

In addition to controlling the sequence in which valves are opened and closed, the controller may be configured to control the duration for which any given valve is opened and the extent to which any given valve is opened. In the latter case, adjustment of the valve may be used to control the duration, pressure and/or volume of a given gas supplied to the process chamber thereby controlling the quantity of gaseous species delivered in a given time. Furthermore, the controller may be configured

to allow a predetermined delay between opening of valves respectively in the first and second valve systems to ensure all gas in an exhaust conduit has been exhausted before new gas is introduced.

The respective pluralities of gas supply conduits, gas exhaust conduits and pumps need not be the same. For example, there may be more gas supply conduits than gas exhaust conduits or pumps, more than one gas being selectively exhausted to the same pump.

The system may further comprise a plurality of gas filled containers connected in fluid communication with the gas supply conduits. Optionally, at least one of the gas filled containers may be filled with a purge gas.

For the purposes of exemplification, an embodiment of the invention will now be further described with reference to the Figures in which:

Figure 1 illustrates a vent-run gas switching system in accordance with the prior art.

Figure 2 illustrates a vent-run gas switching system in accordance with the present invention.

As can be seen from Figure 1 a prior art vent-run gas switching system comprises two gas supplies Gas A and Gas B each connected to a process chamber 11 and pump 12 by means of a series of conduits 13-18. The conduits 13 to 16 include valves which can be operated to control the flow of Gas A and Gas B to the pump 12 via the process chamber 11, or bypassing 17 the process chamber 11. Thus, only one of the gases is supplied to the chamber at any one time.

To supply Gas A to the chamber 11, valved conduit 14 is opened, Gas A flows directly through valved conduit 14 into the chamber 11 and

4

exhausts through conduit 18 to pump 12. During delivery of Gas A, valved conduits 15 and 16 remain closed whilst valved conduit 13 is open. Gas B therefore flows through conduits 13, 17 and 18 to the pump 12 bypassing the chamber. To supply Gas B to the chamber 11, valved conduits 15 and 16 are opened and valved conduits 13 and 14 are closed. In this configuration, Gas B is supplied through conduit 15 to the chamber 11 and exhausted via conduit 18 to the pump 12. Meanwhile, Gas A is supplied through conduits 16, 17 and 18 directly to the pump 12, bypassing the chamber 11.

It will be appreciated that, as both gases pass through conduit 18 and exhaust to the single pump 12, there is scope for cross reaction between residuals of each gas remaining after switching between the gas supplies.

Figure 2 illustrates a vent-run gas switching system in accordance with the present invention.

As can be seen from Figure 2 a vent-run gas switching system comprises three gas supplies Gas 1, Gas 2 and Gas 3. Typically, Gas 1 may be a purge gas and Gas 2 and Gas 3 process gases to be reacted in the process chamber 4 for example, to form a multi-layer conductor semiconductor product, or an multi-layered insulator. Each gas supply is connected to the process chamber 4 and one of two pumps 7, 8 by means of conduits 21, 22, ..., 35. The conduits 25 to 35 include valves which can be operated to control the flow of Gases 1, 2 and 3 to the pumps 7 and 8 via the process chamber 4, or bypassing the process chamber 4.

When valved conduits 25, 26, 27 and 28 are closed and 31 to 35 opened, Gas 2 is supplied directly to the process chamber 4 and exhausted to pump 7. Meanwhile, Gas 1 (a purge gas) is directed to pump 7 through conduits 31 and 21a and b and Gas 3 is directed to pump 8

5

through conduits 23a and b, 33 and 35. As Gas 1 is an inert purge gas, it can safely be mixed with Gas 2 at the foreline of pump 7 as no cross reaction of the gases will occur. Following a supply of Gas 2, the chamber may be purged by a supply of purge gas, Gas 1. This purge is achieved by closing conduits 31 and 32 and opening conduits 25 and 26. Conduits 27 and 28 remain closed as do conduits 29 and 30. Purge gas, Gas 1 is directed through conduits 21a and b and 25 into the process chamber 4 and exhausts to pump 7 through conduits 24 and 34. Gas 2 is directed through conduits 22 and 26 and conduit 21b to the pump 7, bypassing the process chamber 4. Meanwhile Gas 3, continues to pass directly through conduits 23a and b, 33 and 35 to pump 8, bypassing the process chamber 4. Thus the chamber 4 is purged of Gas 2 and Gas 3 can safely be introduced.

Gas 3 is introduced by opening valved conduits 27, 28, 29 and 30. Valved conduits 25, 26, 33, 34 and 35 are closed. Gas 3 is directed through conduits 23a and 28 to process chamber 4 and exhausted to pump 8 via conduits 24 and 29. Gas 2 is directed to pump 7 through conduits 22, 27, 23b and 30 bypassing the process chamber 4. Gas 1 is directed to pump 7 through conduits 31 and 21a and b, bypassing the process chamber 4.

Thus it can be seen, by suitable operation of the valved conduits 25 to 35, each of the three gases Gas 1, Gas 2, Gas 3 can be sequentially supplied to the process chamber 4 whilst the reactive gases 2 and 3 can be fed to separate pumps 7 and 8. As the gases Gas 2 and Gas 3 are diverted to a given pump 7,8 before they reach the pump foreline, there is no opportunity for cross reaction and consequent particulate contamination of the pumps.

It will be appreciated that the described arrangement can easily be extended for more than two reactive gases by adding further valved conduit arrangements and pumps in parallel. It will further be appreciated

6

that separate pumps are only needed where any given two or more gases will cross react with each other. Any two or more gases which will not cross react, can safely be directed to a single pump using the arrangements of the invention.

The foregoing description is purely exemplary of just one embodiment of the invention and is not intended to be restrictive of the true scope of the invention as claimed in the appended claims.

CLAIMS

1. A vent-run gas switching system comprising:
 - a plurality of gas supply conduits in fluid communication with a process chamber; a plurality of gas exhaust conduits in fluid communication with the process chamber; a plurality of pumps each in fluid communication with one or more gas exhaust conduits; a first valve system associated with the plurality of gas supply conduits and configured to control supply of a plurality of gases to the process chamber in sequence;
 - a second valve system associated with the plurality of gas exhaust conduits configured to direct gases exhausted from the process chamber to the pumps, each gas being selectively directable to a pre-selected pump; and
 - one or more gas supply bypass conduits in fluid communication with one or more of the pumps and bypassing the process chamber.
2. A vent-run gas switching system as claimed in claim 1 further comprising a controller for controlling the operation of the first and second valve systems, in use, to supply gases to the process chamber in a pre-selected sequence and exhaust gases, in sequence, to pre-selected pumps.
3. A vent-run gas switching system as claimed in claim 2 wherein the controller is configured to control the duration for which any given valve in the first or second valve system is opened and the extent to which any given valve in the first or second valve system is opened.
4. A vent-run gas switching system as claimed in claim 2 or claim 3 wherein the controller is configured to allow a predetermined delay between opening of valves respectively in the first and second valve

8

systems to ensure all gas in an exhaust conduit has been exhausted before new gas is introduced.

5. A vent-run gas switching system as claimed in any preceding claim further comprising a plurality of gas-filled containers connected in fluid communication with the gas supply conduits.
6. A vent-run gas switching system as claimed in claim 5 wherein at least one of the gas filled containers is filled with a purge gas.
7. A vent-run gas switching system as claimed in any preceding claim wherein the respective pluralities of gas supply conduits and/or gas exhaust conduits and/or pumps differ.
8. A vent-run gas switching system substantially as described herein and with reference to Figure 2.

9

ABSTRACT**VENT-RUN GAS SWITCHING SYSTEMS**

A vent-run gas switching system comprising:

a plurality of gas supply conduits 22, 23, 25, 28, 32, in fluid communication with a process chamber 4; a plurality of gas exhaust conduits 24, 34, 29, in fluid communication with the process chamber 4; a plurality of pumps 7, 8 each in fluid communication with one or more gas exhaust conduits; a first valve system 31, 32, 33, 25, 26, 27, 28 associated with the plurality of gas supply conduits and configured to control supply of a plurality of gases 1, 2, 3 to the process chamber 4 in sequence;

a second valve system 34, 35, 29, 30 associated with the plurality of gas exhaust conduits configured to direct gases 1, 2, 3 exhausted from the process chamber 4 to the pumps 7, 8, each gas being selectively directable to a pre-selected pump; and

one or more gas supply bypass conduits 21b, 23b in fluid communication with one or more of the pumps 7, 8 and bypassing the process chamber 4.

(Fig. 2)




FIG. 1




FIG. 2

PCT/GB02/4121

PCT/GB2004/004121



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ ~~FADED TEXT OR DRAWING~~
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ ~~GRAY SCALE DOCUMENTS~~
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.